



WALL MOUNTED UNIT

Wall mounted unit, offering good value for money

FTXC-E + RXC-E



- Flat, stylish front panel blends easily with any interior décor and is easier to clean
- Onecta app
- Seasonal efficiency values up to A++ in cooling
- Bluevolution range: lower environmental impact



Onecta app



Energy
saving during
standby mode

FTXC-E + RXC-E



Efficiency data			FTXC + RXC	20E + 20E	25E + 25E	35E + 35E	50E + 50E	60E + 60E	71E + 71E
Cooling capacity	Min./Max.		kW	13/3.0		13/4.0	137/6.2	18/7.0	2.3/7.3
Heating capacity	Min./Max.		kW	13/4.0		13/4.8	136/6.6	148/8.0	2.3/9.0
Power input	Cooling	Min./Nom./Max.	kW	0.300/0.595/1.150	0.300/0.765/1.150	0.315/1.045/1.740	0.295/1.550/2.110	0.380/1.890/2.045	0.440/2.380/2.540
	Heating	Min./Nom./Max.	kW	0.275/0.670/1.350	0.275/0.750/1.350	0.275/1.070/1.570	0.270/1.515/1.850	0.325/1.680/2.350	0.500/2.460/2.640
Space cooling	Energy efficiency class			A++					A
	Capacity	Pdesign	kW	2.1	2.6	3.4	5.1	6.2	7.0
	SEER			6.9	6.8	6.9	6.5	6.4	5.3
	Annual energy consumption		kWh/a	106	131	175	276	339	460
Space heating (Average climate)	Energy efficiency class			A+					A
	Capacity	Pdesign	kW	1.9	2.2		3.9	4.1	6.4
	SCOP/A			4.4	4.5	4.3	4.4	4.2	3.8
	Annual energy consumption		kWh/a	595	701	733	1,234	1,353	2,332
Nominal efficiency	EER			3.36	3.35		3.29	3.30	2.98
	COP			3.73	3.79	3.74	3.71	3.81	3.25
	Energy labeling	Cooling/Heating Directive		A/A					C/C
Current - 50Hz	Maximum fuse amps (MFA)		A	16					

Indoor unit				FTXC	20E	25E	35E	50E	60E	71E
Dimensions	Unit	HeightxWidthxDepth		mm	288 x770 x234				297 x990 x273	
Weight	Unit			kg	9.0		9.5		13.0	
Air filter	Type				Removable / washable					
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/ High	m³/min	5.4 /6.1 /8.1 /10.8		5.4 /6.4 /8.7 /11.1		7.4 /8.1 /9.9 /12.5	
									10.2 /12.5 /14.5 /20.4	
Sound power level	Cooling			dBA	57		58		60	
Sound pressure level	Cooling	Silent operation/Low/High		dBA	21 /26 /40		22 /26 /41		30 /33 /47	
Control systems	Infrared remote control				ARC486A6					
	Wired remote control				-					

Outdoor unit				RXC	20E	25E	35E	50E	60E	71E
Dimensions	Unit	HeightxWidthxDepth		mm	550 x658 x273			615 x845 x300		695 x930 x350
Weight	Unit			kg	24		26	39		45
Sound power level	Cooling	Nom.		dBA	58		60	65	66	69
Sound pressure level	Cooling	High		dBA	45		46	51	54	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	10 ~46			-10 ~46		
	Heating	Ambient	Min.~Max.	°CWB				-15 ~18		
Refrigerant	Type				R-32					
	GWP				675					
	Charge			kg/ tCO2Eq	0.55/0.371		0.75/0.506	1.0/0.675	11.0/0.743	115 /0.776
Piping connections	Liquid	OD		mm	6.4					
	Gas	OD		mm	9.52		12.7			
	Piping length	OU - IU	Max.	m	20		30			
		System	Chargeless		m	75				
	Additional refrigerant charge			kg/m	0,017 (for piping length exceeding 7.5m)					
	Level difference	IU - OU	Max.	m	15		20			
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-440					
Current - 50Hz	Maximum fuse amps (MFA)			A	16					

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · België · www.daikin.eu · BE 0412 120 336 · RPR Oostende

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

ECPEN26-012

07/2026

